NSN 5962-01-316-8161

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-316-8161

| Overall Length: |
|--|
| 0.358 inches |
| Overall Height: |
| 0.100 inches |
| Overall Width: |
| 0.358 inches |
| Body Length: |
| 0.358 inches |
| Body Width: |
| 0.358 inches |
| Body Height: |
| 0.088 inches |
| Maximum Power Dissipation Rating: |
| 25.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Bipolar and burn in and cascadable and low power and monolithic and schottky and w/clear and w/clock |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leadless flat pack |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| Dual 4 input |
| Design Function And Quantity: |
| 2 flip-flop, j-k |
| Case Outline Source And Designator: |
| C-2 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Test Data Document: |
| 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

81349-mil-m-38510/301 government specification

NSN 5962-01-316-8161

Digital Microcircuit - Page 2 of 2



| C | ha | Ιf | 1 | ife | |
|---|-----|----|---|-------|--|
| • | ııe | | _ | .II C | |

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0