## NSN 5962-01-317-2034

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-317-2034 **Overall Width:** Between 0.400 inches and 0.420 inches **Body Length:** Between 0.400 inches and 0.420 inches **Body Width:** Between 0.300 inches and 0.330 inches **Body Height:** Between 0.090 inches and 0.110 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and hybrid and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 protector, overvoltage **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 flat leads Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli