

View Online at <https://aerobasegroup.com/nsn/5962-01-317-2042>

**Body Length:**

0.450 inches

**Body Width:**

0.450 inches

**Body Height:**

0.100 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Monolithic and programmable and bipolar

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

20 input

**Design Function And Quantity:**

1 gate, array

**Case Outline Source And Designator:**

C-4 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

5.5 volts power source

**Time Rating Per Characteristic:**

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0