NSN 5962-01-317-2042

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-317-2042

Body Length:
0.450 inches
Body Width:
0.450 inches
Body Height:
0.100 inches
Maximum Power Dissipation Rating:
1.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and programmable and bipolar
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
20 input
Design Function And Quantity:
1 gate, array
Case Outline Source And Designator:
C-4 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 leadless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5962-01-317-2042

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

