NSN 5962-01-317-2056

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-317-2056

Overall Length:
0.358 inches
Overall Height:
0.100 inches
Overall Width:
0.358 inches
Body Length:
0.358 inches
Body Width:
0.358 inches
Body Height:
0.088 inches
Maximum Power Dissipation Rating:
6.1 milliwatts
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Bipolar and burn in and monolithic and positive outputs and schottky
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 4 input
Design Function And Quantity:
2 gate, nand
Case Outline Source And Designator:
C-2 mil-m-38510
Terminal Surface Treatment:
Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

81349-mil-m-38510/300 government specification

NSN 5962-01-317-2056

Digital Microcircuit - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0