NSN 5962-01-317-3936

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-317-3936

Yes - demil/mli
Demilitarization:

Unit Of Measure:
N/a
Shelf Life:
81349-mil-m-38510/126 government specification
Specification Data:
16 printed circuit
Terminal Type And Quantity:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Test Data Document:
37.0 volts power source
Voltage Rating And Type Per Characteristic:
Solder
Terminal Surface Treatment:
D-2 mil-m-38510
Case Outline Source And Designator:
1 modulator, regulator pulse width
Design Function And Quantity:
8 input
Input Circuit Pattern:
Dual-in-line
Inclosure Configuration:
Ceramic
Inclosure Material:
Monolithic
Features Provided:
-65.0/+150.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
Operating Tempurature Range:
250.0 milliwatts
Maximum Power Dissipation Rating:
0.185 inches
Body Height:
0.310 inches
Body Width:
0.840 inches
BOOV LEDOTO:

Fiig: A458a0