NSN 5962-01-318-3767

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-318-3767
Body Length:
Between 0.750 inches and 0.770 inches
Body Width:
Between 0.240 inches and 0.290 inches
Body Height:
Between 0.135 inches and 0.150 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
High performance and low noise and bidirectional and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Catput Logio i cimi
Complementary-metal oxide-semiconductor logic
Complementary-metal oxide-semiconductor logic
Complementary-metal oxide-semiconductor logic Input Circuit Pattern:
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity:
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment:
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Terminal Type And Quantity:
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Terminal Type And Quantity: 16 printed circuit
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life:
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a
Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 13 input Design Function And Quantity: 1 multiplexer/demultiplexer, cmos Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source Terminal Type And Quantity: 16 printed circuit Shelf Life: N/a

Fiig: A458a0