## NSN 5962-01-318-3767

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-318-3767
Body Length:
Between 0.750 inches and 0.770 inches
Body Width:
Between 0.240 inches and 0.290 inches
Body Height:
Between 0.135 inches and 0.150 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
High performance and low noise and bidirectional and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Complementary-metal oxide-semiconductor logic  Input Circuit Pattern:
Input Circuit Pattern:
Input Circuit Pattern: 13 input
Input Circuit Pattern:  13 input  Design Function And Quantity:
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source  Terminal Type And Quantity:
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source  Terminal Type And Quantity:  16 printed circuit
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  -0.5 volts power source and 7.0 volts power source  Terminal Type And Quantity:  16 printed circuit  Shelf Life:
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Terminal Type And Quantity:  16 printed circuit  Shelf Life:  N/a
Input Circuit Pattern:  13 input  Design Function And Quantity:  1 multiplexer/demultiplexer, cmos  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic: -0.5 volts power source and 7.0 volts power source  Terminal Type And Quantity:  16 printed circuit  Shelf Life:  N/a

**Fiig:** A458a0