## NSN 5962-01-318-6011

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-318-6011

Overall Height:

0.400 inches

**Body Length:** 

0.960 inches

**Body Width:** 

Between 0.220 inches and 0.310 inches

**Body Height:** 

Between 0.130 inches and 0.185 inches

**Maximum Power Dissipation Rating:** 

450.0 milliwatts

**Operating Tempurature Range:** 

-55.0 to 125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0 to 150.0 degrees celsius

**Features Provided:** 

Hermetically sealed and burn in and monolithic and positive outputs

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Dual-in-line

**Output Logic Form:** 

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:** 

12 input

**Design Function And Quantity:** 

1 converter, digital to analog

**Case Outline Source And Designator:** 

D-6 mil-m-38510

**Terminal Surface Treatment:** 

Solder

Voltage Rating And Type Per Characteristic:

17.0 volts power source

**Time Rating Per Chacteristic:** 

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:** 

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

18 printed circuit

**Specification Data:** 

81349-mil-m-38510/127 government specification

Shelf Life:

NI/o

## NSN 5962-01-318-6011

Digital-linear Microcircuit - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0