NSN 5962-01-318-6011

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-318-6011

Overall Height:

0.400 inches

Body Length:

0.960 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.130 inches and 0.185 inches

Maximum Power Dissipation Rating:

450.0 milliwatts

Operating Tempurature Range:

-55.0 to 125.0 degrees celsius

Storage Tempurature Range:

-65.0 to 150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and monolithic and positive outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

12 input

Design Function And Quantity:

1 converter, digital to analog

Case Outline Source And Designator:

D-6 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

17.0 volts power source

Time Rating Per Chacteristic:

1000.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

18 printed circuit

Specification Data:

81349-mil-m-38510/127 government specification

Shelf Life:

NI/o

NSN 5962-01-318-6011

Digital-linear Microcircuit - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0