NSN 5962-01-318-6685

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-318-6685

Body Length:
1.490 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
0.217 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and programmable and erasable and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
26 input
Criticality Code Justification:
Feat
Case Outline Source And Designator:
D-10 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 6.25 volts power source
Time Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Special Features:
Nuclear hardness critical item
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

28 printed circuit

NSN 5962-01-318-6685

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0