## NSN 5962-01-319-7418

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-319-7418

Body Length:	
0.440 inches	
Body Width:	
Between 0.245 inches and 0.285 inches	
Body Height:	
Between 0.045 inches and 0.085 inches	
Maximum Power Dissipation Rating:	
827.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Hermetically sealed and burn in and monolithic and positive outputs	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Flat pack	
Output Logic Form:	
Emitter-coupled logic	
Input Circuit Pattern:	
10 input	
Case Outline Source And Designator:	
F-5 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
8.0 volts power source	
Time Rating Per Chacteristic:	
15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, his	gh to low level
output	
Memory Device Type:	
Ram	
Memory Capacity:	
Unknown	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	
Terminal Type And Quantity:	
16 flat leads	
Shelf Life:	
N/a	
Unit Of Measure:	

---

## NSN 5962-01-319-7418

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

