# NSN 5962-01-320-1677

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-320-1677

## **Overall Height:**

0.425 inches

## **Body Length:**

2.096 inches

## Body Width:

Between 0.510 inches and 0.620 inches

#### **Body Height:**

Between 0.155 inches and 0.210 inches

## **Maximum Power Dissipation Rating:**

550.0 milliwatts

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and w/clock and positive outputs

## Inclosure Material:

Ceramic

## Inclosure Configuration:

Dual-in-line

## Output Logic Form:

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

22 input

## **Design Function And Quantity:**

1 multiplier

## Case Outline Source And Designator:

D-5 mil-m-38510

## **Current Rating Per Characteristic:**

2.00 milliamperes reverse current, dc absolute

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

## **Time Rating Per Chacteristic:**

70.00 nanoseconds propagation delay time, low to high level output and 70.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

40 printed circuit

#### Shelf Life:

# NSN 5962-01-320-1677

Digital Microcircuit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

