NSN 5962-01-321-1937

Linear Microcircuit - Page 1 of 1

A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-321-1937

Body Outside Diameter:
Between 0.350 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Kidd class ddg; close in weapon system (ciws-phalanx); ticonderoga class cg (47); spruance class dd (963); austin ship class lpd-4
amphibious transport docks; oliver perry class ffg; nimitz class cvn; arleigh burke class ddg; forrestal class cv; wasp class lhd
Features Provided:
Monolithic
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 regulator, voltage
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source
Special Features:
Weapon system essential
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:
- -
Demilitarization:
Yes - demil/mli
Fila: