NSN 5962-01-322-2724

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-322-2724

| Overall Height: |
|--|
| Between 0.302 inches and 0.352 inches |
| Body Length: |
| Between 0.938 inches and 0.998 inches |
| Body Width: |
| Between 0.306 inches and 0.318 inches |
| Body Height: |
| Between 0.144 inches and 0.176 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Programmable and schottky and bipolar and monolithic and 3-state output |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 10 input |
| Criticality Code Justification: |
| Zzzy |
| Design Function And Quantity: |
| 8 gate, array |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Special Features: |
| Item must comply with requirements of defense supply center columbus production standard no. Lo4283 |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 20 printed circuit |
| Reference Number Differentiating Characteristics: |
| Breference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing |
| and testing specifications available at the dla icp. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5962-01-322-2724

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0