NSN 5962-01-322-3937

Digital Microcircuit - Page 1 of 2



w Opling at https://aerobasegroup.com/psp/5062-01-322-3037 Vie

View Online at https://aerobasegroup.com/nsn/5962-01-322-3937
Body Length:
0.358 inches
Body Width:
0.358 inches
Body Height:
0.100 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Burn in and monolithic and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Octal 1 input
Design Function And Quantity:
4 buffer and 4 driver, line
Case Outline Source And Designator:
C-2 mil-m-38510
Current Rating Per Characteristic:
50.00 milliamperes forward current, peak total value not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
6.0 volts power source
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 leadless
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

Demilitarization:

Yes - demil/mli

NSN 5962-01-322-3937

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

