## NSN 5962-01-323-5816

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-323-5816 **Overall Height:** 0.400 inches **Body Length:** 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.2 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and programmable and monolithic and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 18 input

**Design Function And Quantity:** 

1 gate, array

**Case Outline Source And Designator:** 

D-9 mil-m-38510

**Terminal Surface Treatment:** 

Solder

**Voltage Rating And Type Per Characteristic:** 

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Chacteristic:** 

20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:** 

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:** 

24 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5962-01-323-5816

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0