Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-323-8715

## **Overall Height:**

0.400 inches

#### **Body Length:**

1.280 inches

## Body Width:

Between 0.220 inches and 0.310 inches

#### **Body Height:**

Between 0.140 inches and 0.185 inches

#### **Maximum Power Dissipation Rating:**

1.2 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and programmable and monolithic and ultraviolet erasable and electrostatic sensitive

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

## Output Logic Form:

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

22 input

#### **Design Function And Quantity:**

1 gate, array

#### Case Outline Source And Designator:

D-9 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

# Time Rating Per Chacteristic:

25.00 nanoseconds propagation delay time, low to high level output and 25.00 nanoseconds propagation delay time, high to low level output

# Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

24 printed circuit

## Shelf Life:

N/a

## Unit Of Measure:

# NSN 5962-01-323-8715

Digital Microcircuit - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0

