NSN 5962-01-324-0716

Memory Microcircuit - Page 1 of 2

Yes - demil/mli



standards, etc.).

View Online at https://aerobasegroup.com/nsn/5962-01-324-0716

Body Length:
0.840 inches
Body Width:
0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
739.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5805-01-188-3993 an/ttc-4 () (v)
Features Provided:
Monolithic and bipolar and programmable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Memory Device Type:
Rom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Van damil/mli

NSN 5962-01-324-0716

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

