## NSN 5962-01-324-2455



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-324-2455 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 400.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5805-01-188-3993 central office **Features Provided:** Hermetically sealed and burn in and monolithic and w/resistor and w/strobe **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 2 comparator, differential **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 14.0 volts power source **Time Rating Per Chacteristic:** 90.00 nanoseconds propagation delay time, low to high level output and 60.00 nanoseconds propagation delay time, high to low level output

## Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-324-2455

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0