## NSN 5962-01-324-6607

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-324-6607 **Overall Width:** Between 0.745 inches and 1.025 inches **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 196.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+165.0 degrees celsius **Features Provided:** Monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Emitter-coupled logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 receiver, line **Case Outline Source And Designator:** F-5 mil-m-38510 **Current Rating Per Characteristic:** 150.00 microamperes forward current, nonrepetitive, peak total value microamperes **Terminal Surface Treatment:** Voltage Rating And Type Per Characteristic: 8.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5962-01-324-6607

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0