## NSN 5962-01-325-6251



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-325-6251 **Body Length:** Between 0.342 inches and 0.358 inches **Body Width:** Between 0.342 inches and 0.358 inches **Body Height:** Between 0.060 inches and 0.100 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/clear and monolithic and high speed **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 8 flip-flop, d-type **Case Outline Source And Designator:** C-2 mil-m-38510 **Current Rating Per Characteristic:** -25.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter and 25.00 milliamperes reverse current, dc **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life:

Demilitarization: No

**Unit Of Measure:** 

N/a

## NSN 5962-01-325-6251

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0