NSN 5962-01-327-1228

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-327-1228

Body Length: 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.130 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.1 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and bipolar and programmable and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 16 input **Design Function And Quantity:** 1 gate, array **Case Outline Source And Designator:** D-8 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 12.0 volts power source **Time Rating Per Chacteristic:** 50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-327-1228

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

