

View Online at <https://aerobasegroup.com/nsn/5962-01-327-7555>

Overall Height:

0.400 inches

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.140 inches and 0.185 inches

Maximum Power Dissipation Rating:

264.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Bipolar and low power and schottky and monolithic and 3-state output

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

18 input

Design Function And Quantity:

8 transceiver

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

-12.00 milliamperes peak forward surge current universal and 12.00 milliamperes peak forward surge current megawatts

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0