NSN 5962-01-330-5523

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-330-5523

View Online at https://aerobasegroup.com/nsn/5962-01-330-5523
Body Length:
Between 0.542 inches and 0.558 inches
Body Width:
Between 0.542 inches and 0.558 inches
Body Height:
Between 0.074 inches and 0.086 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and high speed and static operation
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
26 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
45.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Ram
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
32 leadless
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli

Fiig: A458a0