NSN 5962-01-331-2505

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-331-2505 **Body Length:** 1.490 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.165 inches and 0.210 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and ultraviolet erasable and programmed and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 16 input **Current Rating Per Characteristic:** 100.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source **Capitance Rating Per Characteristic:** 6.00 input picofarads and 12.00 output picofarads **Memory Device Type: Eprom Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-331-2505

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0