NSN 5962-01-331-9884

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-331-9884

| Body Length: |
|---|
| 1.290 inches |
| Body Width: |
| Between 0.220 inches and 0.310 inches |
| Body Height: |
| Between 0.140 inches and 0.185 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Programmed and w/clock and w/disable and monolithic |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 16 input |
| Current Rating Per Characteristic: |
| 100.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts power source |
| Memory Device Type: |
| Pal |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |