NSN 5962-01-332-2292

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-332-2292

Overall Width: Between 0.745 inches and 1.025 inches **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** Between 0.045 inches and 0.065 inches **Maximum Power Dissipation Rating:** 178.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and positive outputs and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Emitter-coupled logic **Input Circuit Pattern:** Triple 3 input **Design Function And Quantity:** 3 receiver, line **Case Outline Source And Designator:** F-5 mil-m-38510 **Current Rating Per Characteristic:** 95.00 nanoamperes reverse current, dc microamperes **Terminal Surface Treatment:** Solder **Product Name:** Ecl, triple line receiver Voltage Rating And Type Per Characteristic: 0.0 volts power source and -8.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads

N/a

Shelf Life:

NSN 5962-01-332-2292

Digital Microcircuit - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0