## NSN 5962-01-332-4647

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-332-4647 **Overall Height:** 0.345 inches **Body Length:** Between 1.235 inches and 1.285 inches **Body Width:** Between 0.515 inches and 0.600 inches **Body Height:** Between 0.145 inches and 0.175 inches **Maximum Power Dissipation Rating:** 525.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5895-01-167-7655 receiving set, radio **Features Provided:** Ultraviolet erasable and programmed and hermetically sealed and w/enable and w/buffered output and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts total supply **Memory Device Type:** Prom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-332-4647

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0