NSN 5962-01-333-0238

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-333-0238

| view Online at https://aerobasegroup.com/nsn/0302-01-000-0250 |
|---|
| Body Length: |
| Between 1.400 inches and 1.420 inches |
| Body Width: |
| Between 0.590 inches and 0.600 inches |
| Body Height: |
| 0.095 inches |
| Maximum Power Dissipation Rating: |
| 725.0 milliwatts |
| Operating Tempurature Range: |
| -55.0 to 125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0 to 150.0 degrees celsius |
| End Application: |
| B-2 |
| Features Provided: |
| Electrostatic sensitive and hermetically sealed and burn in and w/enable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 6 input |
| Criticality Code Justification: |
| Feat |
| Design Function And Quantity: |
| 1 converter, analog to digital |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 16.5 volts power source |
| Special Features: |
| Hardness critical item |
| Nuclear Hardness Critical Feature: |
| Hardened |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 28 printed circuit |
| Shelf Life: |

N/a

NSN 5962-01-333-0238

Digital-linear Microcircuit - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0