NSN 5962-01-333-2334



Linear Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-333-2334 **Body Length:** 0.405 inches **Body Width:** Between 0.290 inches and 0.320 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Kjoint stars target system; aircraft, f-16; ta-4j aircraft; aircraft, b-2 bomber (atb); aircraft, hornet f/a-18; aircraft, harrier av-8b; aircraft, hercules c-130; aircraft, eagle f-15; guided missile, intercept **Features Provided:** Burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 1 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 2 driver **Case Outline Source And Designator:** D-4 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 15.0 volts power source **Special Features:** Weapon system essential **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 printed circuit

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-333-2334

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0