## NSN 5962-01-333-2334

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-333-2334

Body Length:
0.405 inches
Body Width:
Between 0.290 inches and 0.320 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Kjoint stars target system; aircraft, f-16; ta-4j aircraft; aircraft, b-2 bomber (atb); aircraft, hornet f/a-18; aircraft, harrier av-8b; aircraft,
hercules c-130; aircraft, eagle f-15; guided missile, intercept
Features Provided:
Burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Dual 1 input
Criticality Code Justification:
Design Function And Quantity:
2 driver
Case Outline Source And Designator:
D-4 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
15.0 volts power source Special Features:
Weapon system essential
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
8 printed circuit
Shelf Life:
N/a
Unit Of Measure:

---

## NSN 5962-01-333-2334

Linear Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

