## NSN 5962-01-333-7738

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-333-7738

| <b>Maximum Power Dissipation Rating:</b>    |
|---|
| 1.25 watts                                  |
| Operating Tempurature Range:                |
| -40.0/+150.0 degrees celsius                |
| Storage Tempurature Range:                  |
| -40.0/+150.0 degrees celsius                |
| End Application:                            |
| 5865-01-188-3309 jammer system, respo       |
| Features Provided:                          |
| Monolithic and low current                  |
| Inclosure Material:                         |
| Plastic                                     |
| Inclosure Configuration:                    |
| Quad-in-line                                |
| Input Circuit Pattern:                      |
| 3 input                                     |
| Design Function And Quantity:               |
| 1 amplifier, audio frequency                |
| Terminal Surface Treatment:                 |
| Solder                                      |
| Voltage Rating And Type Per Characteristic: |
| 18.0 volts power source                     |
| Terminal Type And Quantity:                 |
| 14 pin                                      |
| Shelf Life:                                 |
| N/a   |
| Unit Of Measure:                            |
|   |
| Demilitarization:                           |
| Yes - demil/mli                             |
| Fiig:                                       |
| A458a0                                      |
|   |
|   |