NSN 5962-01-334-0132

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-334-0132 **Body Length:** 0.640 inches **Body Width:** 0.420 inches **Body Height:** 0.090 inches **Maximum Power Dissipation Rating:** 650.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and programmable **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 12 input **Case Outline Source And Designator:** F-6 mil-m-38510 **Current Rating Per Characteristic:** -200.00 milliamperes reverse current, dc **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Memory Device Type:** Prom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 flat leads Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5962-01-334-0132

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0