# NSN 5962-01-334-6780

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-334-6780

# Body Length:

0.960 inches

# Body Width:

Between 0.220 inches and 0.310 inches

### **Body Height:**

Between 0.140 inches and 0.185 inches

## **Maximum Power Dissipation Rating:**

400.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and monolithic and electrostatic sensitive and positive outputs

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

P-type metal oxide-semiconductor logic

### Input Circuit Pattern:

9 input

#### **Design Function And Quantity:**

1 translator, level

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

7.0 volts power source

#### **Time Rating Per Chacteristic:**

120.00 nanoseconds propagation delay time, low to high level output and 120.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

18 printed circuit

#### Shelf Life:

N/a

# Unit Of Measure:

--

### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0