# NSN 5962-01-335-9176

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-335-9176

### **Body Length:**

Between 0.342 inches and 0.358 inches

#### **Body Width:**

Between 0.342 inches and 0.358 inches

### **Body Height:**

Between 0.064 inches and 0.100 inches

## **Maximum Power Dissipation Rating:**

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and electrostatic sensitive and high speed

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Leadless flat pack

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

8 input

#### **Design Function And Quantity:**

6 buffer and 2 driver, line

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

6.5 volts power source

#### **Special Features:**

Nuclear hardness critical items

#### **Nuclear Hardness Critical Feature:**

Hardened

# Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# Terminal Type And Quantity:

20 leadless

# Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

# NSN 5962-01-335-9176

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

