## NSN 5962-01-335-9178

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-335-9178 **Body Length:** 0.350 inches **Body Width:** 0.350 inches **Body Height:** 0.100 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and high speed and hermetically sealed and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 gate, logic **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 175.00 nanoseconds propagation delay time, low to high level output and 175.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life: N/a

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

Fiig:

A458a0