## NSN 5962-01-336-3382

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-336-3382

Body Length:
1.060 inches
Body Width:
0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
1.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Radiation sensitive and burn in and monolithic and programmable and electrostatic sensitive
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
16 input
Design Function And Quantity:
1 array, logic
Case Outline Source And Designator:
D-8 mil-m-38510
Current Rating Per Characteristic:
70.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Capitance Rating Per Characteristic:
7.00 input picofarads and 7.00 output picofarads
Time Rating Per Chacteristic:
20.00 nanoseconds input
Supplementary Features:
8output and-or invert
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:

20 printed circuit

## NSN 5962-01-336-3382

Digital Microcircuit - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A458a0