NSN 5962-01-338-1291

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-338-1291 **Overall Height:** 0.425 inches **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.150 inches and 0.210 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5895-01-177-0791 receiver-transmitte **Features Provided:** Hermetically sealed and burn in and ultraviolet erasable and programmed **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Case Outline Source And Designator:** D-3 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 6.0 volts power source **Memory Device Type:** Prom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a

--

Unit Of Measure:

NSN 5962-01-338-1291

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0