NSN 5962-01-339-1696

Memory Microcircuit - Page 1 of 2

20 printed circuit



View Online at https://aerobasegroup.com/nsn/5962-01-339-1696

| Overall Length: |
|--|
| 1.060 inches |
| Overall Height: |
| 0.400 inches |
| Body Length: |
| 1.060 inches |
| Body Width: |
| Between 0.220 inches and 0.310 inches |
| Body Height: |
| Between 0.130 inches and 0.185 inches |
| Maximum Power Dissipation Rating: |
| 2.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Bipolar and programmed and w/clock and monolithic and high impedance |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 10 input |
| Case Outline Source And Designator: |
| D-8 mil-m-38510 |
| Current Rating Per Characteristic: |
| 180.00 milliamperes reverse current, dc absolute |
| Terminal Surface Treatment: |
| Solder |
| Product Name: |
| Registered and-or gate array |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 12.0 volts power source |
| Memory Device Type: |
| Pal |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |

NSN 5962-01-339-1696

Memory Microcircuit - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0