

View Online at <https://aerobasegroup.com/nsn/5962-01-339-1705>

**Overall Height:**

Between 0.325 inches and 0.400 inches

**Body Length:**

1.060 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.130 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

2.0 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Bipolar and monolithic and hermetically sealed and burn in

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Case Outline Source And Designator:**

D-8 mil-m-38510

**Current Rating Per Characteristic:**

180.00 milliamperes supply

**Terminal Surface Treatment:**

Solder

**Product Name:**

Registered and-or gate array

**Voltage Rating And Type Per Characteristic:**

-500.0 millivolts power source and 12.0 volts power source

**Time Rating Per Characteristic:**

25.00 nanoseconds propagation delay

**Memory Device Type:**

Programmed

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufacturer standards, etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0