NSN 5962-01-340-1776

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-340-1776

Body Length:	
1.290 inches	
Body Width:	
0.610 inches	
Body Height:	
0.150 inches	
Maximum Power Dissipation Rating:	
1.0 watts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Schottky and programmed and bipolar	
Inclosure Material:	
Ceramic	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
14 input	
Case Outline Source And Designator:	
D-3 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
7.0 volts input	
Time Rating Per Chacteristic:	
100.00 nanoseconds propagation delay time, high to low level output and 100.00 nanose	econds propagation delay time, low to high level
output	
Memory Device Type:	
Prom	
Memory Capacity:	
Unknown	
Terminal Type And Quantity:	
24 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	

NSN 5962-01-340-1776

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

