## NSN 5962-01-340-1848

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-340-1848 **Body Length:** 0.909 inches **Body Width:** 0.909 inches **Body Height:** 0.066 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Leaded chip carrier **Output Logic Form:** Transistor-transistor logic **Design Function And Quantity:** 1 control, memory access **Current Rating Per Characteristic:** 75.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Custom mil-std-1553 direct memory access controller **Voltage Rating And Type Per Characteristic:** -0.3 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds delay **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 64 flat leads Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** Yes - demil/mli

## NSN 5962-01-340-1848

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0