## NSN 5962-01-340-2098

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-340-2098

Body Length:
1.060 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.130 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
3-state output and w/enable and w/disable and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
8 flip-flop, d-type
Case Outline Source And Designator:
D-8 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 6.0 volts power source
Time Rating Per Chacteristic:
10.00 nanoseconds propagation delay time, high to low level output and 12.60 nanoseconds propagation delay time, low to high level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0