## NSN 5962-01-340-8440

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-340-8440

Overall Length:
0.840 inches
Overall Height:
0.400 inches
Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
W/enable and high impedance and monolithic and w/disable and w/resistor
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
10 input
Design Function And Quantity:
4 receiver, line differential
Case Outline Source And Designator:
D-2 mil-m-38510
Current Rating Per Characteristic:
70.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
53.00 nanoseconds propagation delay time, high to low level output and 53.00 nanoseconds propagation delay time, low to high level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:

N/a

## NSN 5962-01-340-8440

Linear Microcircuit - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A458a0