NSN 5962-01-340-9339

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-340-9339

| Maximum Power Dissipation Rating: |
|--|
| 500.0 milliwatts |
| Operating Tempurature Range: |
| 55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| 65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and burn in, mil-std-883, class b |
| nclosure Material: |
| Ceramic |
| nclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| nput Circuit Pattern: |
| Octal 1 input |
| Criticality Code Justification: |
| Feat |
| Design Function And Quantity: |
| 3 flip-flop, d-type |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 7.0 volts input |
| Special Features: |
| tem must comply with requirements of defense electronics supply center production standard no. L04400; for navy nuclear propulsion plant |
| products only |
| Terminal Type And Quantity: |
| 20 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Filg: |
| A458a0 |
| |
| |