

View Online at <https://aerobasegroup.com/nsn/5962-01-340-9340>

**Overall Height:**

0.400 inches

**Body Length:**

0.785 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

500.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and monolithic and bipolar

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Complementary-metal oxide-semiconductor logic

**Input Circuit Pattern:**

Triple 3 input

**Design Function And Quantity:**

3 gate, or

**Case Outline Source And Designator:**

D-1 mil-m-38510

**Current Rating Per Characteristic:**

500.00 milliamperes output

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-500.0 millivolts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

175.00 nanoseconds propagation delay time, high to low level output

**Special Features:**

Nuclear hardness critical items

**Nuclear Hardness Critical Feature:**

Hardened

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

14 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0