## NSN 5962-01-341-1567

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-1567 **Body Length:** 1.060 inches **Body Width:** 0.310 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** High speed and monolithic and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Design Function And Quantity:** 8 transceiver **Case Outline Source And Designator:** D-8 mil-m-38510 **Terminal Surface Treatment:** Solder **Product Name:** Microcircuit, digital, high-speed cmos, octal bus transceiver, three-state, ttl compatible, monolithic silicon **Voltage Rating And Type Per Characteristic:** -0.5 volts input and 7.0 volts input **Special Features:** Recommended operating supply voltage (vcc) 4.5 to 5.5 vdc **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## **NSN 5962-01-341-1567**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0