## NSN 5962-01-341-2442

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-341-2442 **Overall Height:** 0.400 inches **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and high speed and w/resistor **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** D-4 mil-m-38510 **Current Rating Per Characteristic:** 30.00 nanoamperes input bias current over operating temp range **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 44.0 volts total supply **Time Rating Per Chacteristic:** 30.00 microseconds settling **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit

**Unit Of Measure:** 

N/a

Shelf Life:

## NSN 5962-01-341-2442

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0