NSN 5962-01-341-2443



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-341-2443 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 150.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/clock and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 4 input **Design Function And Quantity:** 1 gate, array **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 10.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:**

Solder

Product Name:

Custom gate array, phase shifter

Voltage Rating And Type Per Characteristic:

15.0 volts power source

Capitance Rating Per Characteristic:

Err-060

Time Rating Per Chacteristic:

200.00 nanoseconds propagation delay

Unpackaged Unit Weight:

2.2 grams

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

NSN 5962-01-341-2443

Digital Microcircuit - Page 2 of 2



Terminal Type	And	Quantity:
---------------	-----	-----------

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0